

	ELECTRICAL SPECIFICATIONS				Weight	DIMENSION		
Туре	Group	C20 (Ah)	Reserve capacity (Min)	CCA -18°C (A)	(Kg)	LxWxH (mm)		
EFB - 18 MONTHS WARRANTY								
JEFB60	L2	60	95	510	16,5	245	175	190
JEFB70	L3	70	120	550	18,0	275	175	190
JEFB80D20	D20	80	140	600	19,3	295	175	190
JEFB80	L4	80	140	600	21,0	315	175	190
JEFB95	L5	95	180	700	23,5	360	175	190
EFB - 24 MONTHS WARRANTY								
JEFB62	L2	62	100	520	16,9	245	175	190
JEFB72	L3	72	125	570	18,5	275	175	190
JEFB82	L4	80	145	630	21,5	315	175	190
JEFB97	L5	95	190	750	24,0	360	175	190





The JET Enhaced Flooded Battery (EFB) is perfectly suited for light vehicles with standard Start/Stop systems which operate at a partial state of charge and do not require the deep-cycling characteristics of an AGM battery. Our technology with improved plates are produced with the addition of special materials in both positive and negative plates in order to reach the durability, autonomy and power required for this class of application.

## MAIN BENEFITS

- Improved EFB technology;
- Using of nanotechnology;
- Excellent for standard Start/Stop systems;
- Supports extended engine-off periods;
- High starting power;
- High cycling performance;
- Improved charge acceptance;
- Sealed maintenance free SMF;
- Long service life and reliability.
- BATERIASJET.COM.BR

